

Двигатели постоянного тока серии 4П

Характеристики:

Тип двигателя	Номинальная мощность кВт		Номинальное напряжение В	Частота вращения мин-1	К.П.Д., %			
	УХЛ4	04						
4ПО100S1	0,37	0,33	110	750-1950	60,5			
	0,55	0,50	220	1000-2600	60			
	0,75	0,67		1500-3900	70			
	1,0	1,1		2200-4000	74			
	1,6	1,45		3000-4000	75			
4ПО100S2	0,55	0,5		220	750-1950	60		
			62					
	0,75	0,675	1000-2600		66			
	1,1	1,0	1500-3900		75			
	1,5	1,35	2200-4000		76			
	2,2	2,0	3000-4000		77			
4ПО100L1	0,75	0,675	220	750-1950	67			
					1,1	1,0	1000-2600	68
					1,5	1,35	1500-3900	74
					2,2	2,0	2200-4000	76
					3,0	2,7	3000-4000	80
4ПО112M1	1,5	1,35	220	1000-2600	75			
					71			
	2,2	2,0		1500-3900	76			
	3,0	2,7		2200-4000	77			

	4,0	3,6		3000-4000	80
4П0112М2	1,5			1000-2600	71
	2,2	2,0			75
	2,5	2,25		1500-3900	78
	3,0	2,7			77
	2,5				
	4,0	3,6		2200-4000	79
	3,0			3000-4000	
	5,5	5,0			83
			440		
	1,5	1,35	110		76
4ПБ100S1	0,25	0,225	220	750-1950	58
	0,37	0,33		1000-2600	63
	0,55	0,50		1500-3900	67,5
	0,75	0,675		2200-4000	71
	1,1	1,0		3000-4000	73
4ПБ100S2	0,37	0,33		750-1950	58
	0,55	0,50		1000-2600	70
	0,75	0,675		1500-3900	72
	1,1	1,0		2200-4000	74
	1,5	1,35		3000-4000	77
4ПБ100L1	0,45	0,405		750-1950	60
	0,6	0,54		1000-2600	65
	1,1	1,0		1500-3900	73
	1,3	1,17		2200-4000	74
	1,8	1,62		3000-4000	78
4ПБ100M1	0,55	0,5		750-1950	62
	0,75	0,675		1000-2600	66

	1,3	1,17		1500-3900	72
	1,5	1,35		2200-4000	80
	2,2	2,0		3000-4000	82
4ПБ100М2	1,0	0,9		1000-2600	69
					72
	1,5	1,35		1500-3900	79
	1,7		220	1000	75
	2,2	2,0	110	2200-4000	77,4
			220		
	3,0	2,7	220	3000-4000	85
	4,0				83
	5,5				